

Features:

- Okuma #OSP5000L-G Control.
 - Graphics / IGF.
 - 8" Power Chuck.
 - 12-Station Turret.
 - Coolant System.
 - 5C Nose Piece.
 - Chip Conveyor.
 - Includes all tooling shown in pictures.
-

Specifications:

Capacities:

Number of Controlled Axes: 2

Nominal Size: 9.84" x 19.69"

Swing Over Bed: 15.75"

Maximum Turning Diameter x Maximum Work Length (Chuck Work): 9.84" x 9.06"

Maximum Turning Diameter x Maximum Work Length (Shaft Work): 9.84" x 19.69"

Main Spindle:

Spindle Diameter at Front Bearing: 3.94"

Bore Diameter: 2.20"

Spindle Mount: ASA A2-6

Internal Taper: #6 Morse Taper

Range of Spindle Speeds: 70 - 4,200 rpm

Number of Spindle Speeds: Auto. 2 range x infinitely variable

Carriage (Z-Axis):

Longitudinal Travel: 20.47"

Cutting Feedrates: 0.0001 - 40.0000 ipr

Rapid Traverse Speed: 472 ipm

Cross Slide (X-Axis):

Cross Slide Travel: 4.92" + 0.59"

Cutting Feedrates: 0.0001 - 40.0000 ipr

Rapid Traverse Speed: 472 ipm

Turret:

Number of Tool Stations: 12

Size of OD Turning Tool: 1" x 1"

Size of ID Turning Tool: 1-1/2"

Bed:

Length of Slideway: 46.06"

Width of Slideway: 15.35"

Tailstock:

Diameter of Quill: 3.54"

Taper of Center: #5 Morse Taper

Quill Stroke: 4.72"

General:

Main Spindle Drive Motor: 15 / 10 Horsepower (30 min. / continuous)

Electrical: 220 / 440 Volt, Three Phase

Overall Dimensions: 156" x 75" x 72" tall